

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-27 Cancelled.

28. (new) A container assembly comprising:

a container body having an upper open end and a lower open end, said upper open end having an upper neck, said lower open end having a lower neck with a rim, said upper neck having a first securing structure, said lower neck having a second securing structure;

a bottom cap having a bottom wall and a side wall, said bottom wall having a central portion, a peripheral portion and a plurality of holes disposed completely through said bottom wall, said central portion being surrounded by said peripheral portion and recessed towards said upper open end, said side wall extending upwardly from said peripheral portion, said side wall having a third securing structure that removably engages with said second securing structure for securing said bottom cap to said container body; and

a sealing member being disposed between said rim of said lower neck and said bottom cap when said bottom cap is connected to said container body, wherein said bottom cap is made of a first material, said sealing member is made of a second material, and said second material is flexible.

29. (new) The container assembly of claim 28, wherein said sealing member covers said plurality of holes.

30. (new) The container assembly of claim 28, wherein said peripheral portion is substantially flat.

31. (new) The container assembly of claim 28, wherein said first and second securing structures are threads, wherein said side wall has a surface, and wherein said third securing structure is threads formed on said surface of said side wall.

32. (new) The container assembly of claim 28, wherein said second material has a Shore A Hardness about 30 to about 60.

33. (new) The container assembly of claim 28, wherein said central portion has a dome-like shape.

34. (new) The container assembly of claim 28, wherein said container body has a first outer surface above said lower neck, wherein said side wall has a second outer surface, and wherein said first outer surface is substantially contiguous with said second outer surface when said bottom cap is connected to said container body.

35. (new) The container assembly of claim 34, wherein said side wall comprises an inner wall, an outer wall and a space therebetween.

36. (new) The container assembly of claim 28, wherein said container body has a first outer diameter, wherein said upper neck has a second outer diameter, wherein said lower neck has a third outer diameter, and wherein said first outer diameter is larger

than said second and third outer diameters.

37. (new) The container assembly of claim 28, wherein said bottom cap has a center point, and wherein said plurality of holes is arranged in a circular pattern that is concentrically aligned with said center point of said bottom cap.

38. (new) The container assembly of claim 28, wherein said rim has an inwardly extending flange.

39. (new) The container assembly of claim 38, wherein said flange is orthogonal to said side wall.

40. (new) The container assembly of claim 28, wherein said sealing member has an upper surface and a lower surface, and wherein said upper and lower surfaces of said sealing member are non-planar.

41. (new) The container assembly of claim 28, wherein said plurality of holes are substantially equi-distantly spaced apart.

42. (new) A container assembly comprising:

a container body having an upper open end and a lower open end, said upper open end having an upper neck of reduced diameter, said lower open end having a lower neck of reduced diameter, said lower neck having a rim, said upper neck having first threads, said lower neck having second threads;

a bottom cap having a bottom wall and a side wall, said bottom wall having a central portion, a peripheral portion and a plurality of holes disposed completely through said bottom wall, said central portion being surrounded by said peripheral portion

and recessed towards said upper open end, said side wall extending upwardly from said peripheral portion, said side wall having third threads that removably connect with said second threads for securing said bottom cap to said container body; and

a sealing member being disposed between said rim of said lower neck and said bottom cap when said bottom cap is connected to said container body, wherein said sealing member covers said plurality of holes and is flexible, and wherein said bottom cap is made of a first material and said sealing member is made of a second material.

43. (new) The container assembly of claim 42, wherein said second material has a Shore A Hardness about 30 to about 60.

44. (new) The container assembly of claim 42, wherein said bottom cap has a center point, and wherein said plurality of holes is arranged in a circular pattern that is concentrically aligned with said center point of said bottom cap.

45. (new) The container assembly of claim 42, wherein said sealing member has an upper surface and a lower surface, and wherein said upper and lower surfaces of said sealing member are non-planar.

46. (new) The container assembly of claim 42, wherein said plurality of holes are substantially equi-distantly spaced apart.

47. (new) A container assembly comprising:

a container body having an upper open end and a lower open end, said upper open end having an upper neck of reduced diameter, said lower open end having a lower neck of reduced diameter, said

lower neck having a rim, said upper neck having first threads, said lower neck having second threads;

a bottom cap having a bottom wall and a side wall, said bottom wall having a central portion, a peripheral portion and a plurality of holes disposed completely through said bottom wall, said central portion being surrounded by said peripheral portion and recessed towards said upper open end, said side wall extending upwardly from said peripheral portion, said side wall having third threads that removably connect with said second threads for securing said bottom cap to said container body; and

a sealing member being disposed between said rim of said lower neck and said bottom cap when said bottom cap is connected to said container body, wherein said bottom cap is made of a first material, wherein said sealing member covers said plurality of holes that are substantially equi-distantly spaced apart, is made of a second material, and is flexible, and wherein said sealing member has upper and lower surfaces that are non-planar.